

DUCTILE IRON GRATINGS

GM325G - GALVAGRATE® DROP-IN GRATE - CLASS D

PRODUCT CODE	CLEAR OPENING		FRAME			GRATE				MASS OF FRAME KG	TOTAL MASS OF GRATE/S KG	BOLTDOWN BOLTS (QTY)
	CO (W)	CO (L)	OVERALL FRAME WIDTH	OVERALL FRAME LENGTH	FRAME DEPTH	GRATE WIDTH	OVERALL GRATE LENGTH	GRATE BELLY DEPTH (MAX)	GRATE SEATING DEPTH			
GM325G66DGAL	610	610	822	710	65	690	600	77	59	12	42	2
GM325G99DGAL	910	910	1122	1010	65	990	900	93	59	17	88	2
GM325G96DGAL	925	610	1117	690	63	990	600	105	59	11	57	2
GM325G7510DVGAL	1000	750	1300	850	75	1075	735	130	70	19	96	2
GM325G69DGAL	625	910	817	990	63	690	900	77	59	11	60	2
GM325G1212DGAL	1200	1215	1392	1295	63	1265	1200	125	59	17	162	4

Note:

- Grate and frame come assembled and bolted with M12 SS SHC Bolts (Refer table for quantity)
- Trench lengths can be made to custom requirements
- Grates and frames come as galvanised to AS/NZS 4680 (Grates with bitumen coating may be available upon request)

GM325G94DGALSE - GALVAGRATE® SIDE ENTRY - CLASS D

PRODUCT CODE	CLEAR OPENING		FRAME			GRATE				MASS OF FRAME KG	TOTAL MASS OF GRATE/S KG	BOLTDOWN BOLTS (QTY)
	CO (W)	CO (L)*	OVERALL FRAME WIDTH	OVERALL FRAME LENGTH	FRAME DEPTH	GRATE WIDTH	OVERALL GRATE LENGTH	GRATE BELLY DEPTH (MAX)	GRATE SEATING DEPTH			
GM325G94DGALSE	914	462	1134	512	65	989	457	95	59	9	58	2

Note:

- Grate and frame come assembled and bolted with M10 SS SHC Bolts (Refer table for quantity)
- Grate and frame come as galvanised to AS/NZS 4680 (Grates with bitumen coating may be available upon request)

The information contained in this document should serve as a guide only and is subject to change without notice. For more information please contact Iplex Pipelines Australia Pty Ltd.



DUCTILE IRON GRATINGS

GM325V - GALVAGRATE® V-TYPE - CLASS D

PRODUCT CODE	CLEAR OPENING		FRAME			GRATE				MASS OF FRAME KG	TOTAL MASS OF GRATE/S KG	BOLTDOWN BOLTS (QTY)	*VARIABLE ANGLE (Y/N)
	CO (W)	CO (L)*	OVERALL FRAME WIDTH	OVERALL FRAME LENGTH	FRAME DEPTH	GRATE WIDTH	OVERALL GRATE LENGTH	GRATE BELLY DEPTH (MAX)	GRATE SEATING DEPTH				
GM325V66DGAL	610	620	830	720	65	685	610	70	59	13	51	4	YES
GM325V94DGAL	900	404	1000	504	65	984	401	90	60	12	61	2	NO
GM325V96DGAL	914	620	1134	720	65	989	610	85	59	15	75	4	YES
GM325V99DGAL	914	924	1134	1024	65	989	914	95	59	18	115	4	YES

Note:

- Grate and frame come assembled and bolted with M12 SS SHC Bolts (Refer table for quantity)
- Trench lengths can be made to custom requirements
- Grates and frames come as galvanised to AS/NZS 4680 (Grates with bitumen coating may be available upon request)
- *Refer table for length and angle variation details

The information contained in this document should serve as a guide only and is subject to change without notice. For more information please contact Iplex Pipelines Australia Pty Ltd.

