



# STANDARDSMARK LICENCE

SAI Global hereby grants:

## AVK Australia Holding Pty Ltd

ABN 11 081 236 777

559A Grand Junction Road, Wingfield, SA 5013, Australia

### StandardsMark Licence

Manufactured to:

**AS/NZS 2638.2:2011 - Gate valves for waterworks purposes - Resilient seated  
& AS/NZS 2638.1:2011 - Gate valves for waterworks purposes - Metal seated**

"the StandardsMark Licensee" the right to use the STANDARDSMARK as shown below only in respect of the goods described and detailed in the Schedule which are produced by the Licensee or on behalf of the Licensee\* and which comply with the appropriate Standard referred to above as from time to time amended. The Licence is granted subject to the rules governing the use of the STANDARDSMARK and the Terms and Conditions for certification and licence. The Licensee covenants to comply with all the Rules and Terms and Conditions.

**Licence No:** SMK02420

**Issued :** 6 May 2020

**Expires :** 9 December 2024

**Originally Certified :** 9 May 2000

**Current Certification :** 5 May 2020

Heather Mahon  
General Manager Technical Services  
SAI Global Assurance



Australian  
Standard



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to [www.saiglobal.com](http://www.saiglobal.com), for the list of product models.

 **SAI GLOBAL**  
INFORM. INSPIRE. IMPROVE.

# SCHEDULE TO STANDARDSMARK LICENCE

SAI Global hereby grants:

## AVK Australia Holding Pty Ltd

559A Grand Junction Road, Wingfield, SA 5013, Australia

StandardsMark Licence

Manufactured to:

**AS/NZS 2638.1:2011 - Gate valves for waterworks purposes - Metal seated**

Model identification of the goods on which the STANDARDSMARK may be used:

| Model Identification    | Brand Name | Nominal Size | Product Description           | Product Type            | Valve class (Allowable operating Pressure) | Max Operating Temperature | End Connection Designation | Date Endorsed |
|-------------------------|------------|--------------|-------------------------------|-------------------------|--------------------------------------------|---------------------------|----------------------------|---------------|
| 2580/90 2580/92 2580/98 | Sureflow   | DN 200       | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 2580/90 2580/92 2580/98 | Sureflow   | DN 225       | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 2580/90 2580/92 2580/98 | Sureflow   | DN 250       | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 2580/90 2580/92 2580/98 | Sureflow   | DN 150       | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 2580/90 2580/92 2580/98 | Sureflow   | DN 300       | DN300 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 2580/90 2580/92 2580/98 | Sureflow   | DN 080       | DN080 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 2580/90 2580/92 2580/98 | Sureflow   | DN 100       | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 580/90 580/92 580/98    | AVK        | DN 300       | DN300 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 580/90 580/92 580/98    | AVK        | DN 200       | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 580/90 580/92 580/98    | AVK        | DN 225       | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 580/90 580/92 580/98    | AVK        | DN 250       | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 580/90 580/92 580/98    | AVK        | DN 080       | DN080 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 580/90 580/92 580/98    | AVK        | DN 100       | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| 580/90 580/92 580/98    | AVK        | DN 150       | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 70°C                      | Flange x Flange            | 17 Jul 2019   |
| A0412/2-039 DN100       | AVK        | DN 100       | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |
| A0412/2-040 DN150       | AVK        | DN 150       | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |
| A0412/2-041 DN200       | AVK        | DN 200       | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |
| A0412/2-042 DN225       | AVK        | DN 225       | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |
| A0412/2-043 DN250       | AVK        | DN 250       | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |
| A0412/2-044 DN100       | AVK        | DN 100       | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Spigot x Spigot            | 12 Feb 2019   |
| A0412/2-045 DN150       | AVK        | DN 150       | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Spigot x Spigot            | 12 Feb 2019   |
| A0412/2-046 DN80        | AVK        | DN 80        | DN80 Metal Seated Gate Valve  | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-047 DN100       | AVK        | DN 100       | DN100 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-048 DN150       | AVK        | DN 150       | DN150 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-049 DN200       | AVK        | DN 200       | DN200 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-050 DN225       | AVK        | DN 225       | DN225 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-051 DN250       | AVK        | DN 250       | DN250 Metal Seated Gate Valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Brand Name | Nominal Size | Product Description                             | Product Type            | Valve class (Allowable operating Pressure) | Max Operating Temperature | End Connection Designation | Date Endorsed |
|----------------------|------------|--------------|-------------------------------------------------|-------------------------|--------------------------------------------|---------------------------|----------------------------|---------------|
| A0412/2-052<br>DN300 | AVK        | DN 300       | DN300 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-053<br>DN375 | AVK        | DN 375       | DN375 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-054<br>DN450 | AVK        | DN 450       | DN450 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-055<br>DN500 | AVK        | DN 500       | DN500 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-056<br>DN600 | AVK        | DN 600       | DN600 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-057<br>DN750 | AVK        | DN 750       | DN750 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-065<br>DN80  | AVK        | DN 80        | DN80 Metal Seated Gate Valve                    | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-066<br>DN100 | AVK        | DN 100       | DN100 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-067<br>DN150 | AVK        | DN 150       | DN150 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-068<br>DN200 | AVK        | DN 200       | DN200 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-069<br>DN225 | AVK        | DN 225       | DN225 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-070<br>DN250 | AVK        | DN 250       | DN250 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-071<br>DN300 | AVK        | DN 300       | DN300 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-072<br>DN375 | AVK        | DN 375       | DN375 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-073<br>DN450 | AVK        | DN 450       | DN450 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-074<br>DN500 | AVK        | DN 500       | DN500 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-075<br>DN600 | AVK        | DN 600       | DN600 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-076<br>DN750 | AVK        | DN 750       | DN750 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-078<br>DN100 | AVK        | DN 100       | DN100 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Victaulic x Victaulic      | 12 Feb 2019   |
| A0412/2-079<br>DN150 | AVK        | DN 150       | DN150 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Victaulic x Victaulic      | 12 Feb 2019   |
| A0412/2-095<br>DN375 | AVK        | DN 375       | DN375 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-096<br>DN375 | AVK        | DN 375       | DN375 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-097<br>DN500 | AVK        | DN 500       | DN500 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-098<br>DN500 | AVK        | DN 500       | DN500 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-099<br>DN600 | AVK        | DN 600       | DN600 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-100<br>DN600 | AVK        | DN 600       | DN600 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-101<br>DN750 | AVK        | DN 750       | DN750 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-102<br>DN750 | AVK        | DN 750       | DN750 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-103<br>DN450 | AVK        | DN 450       | DN450 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-104<br>DN450 | AVK        | DN 450       | DN450 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-109<br>DN900 | AVK        | DN 900       | DN900 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-112<br>DN900 | AVK        | DN 900       | DN900 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-115<br>DN900 | AVK        | DN 900       | DN900 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| A0412/2-116<br>DN900 | AVK        | DN 900       | DN900 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-039<br>DN100 | Sureflow   | DN 100       | DN100 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |
| S0412/2-040<br>DN150 | Sureflow   | DN 150       | DN150 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Brand Name | Nominal Size | Product Description                             | Product Type            | Valve class (Allowable operating Pressure) | Max Operating Temperature | End Connection Designation | Date Endorsed |
|----------------------|------------|--------------|-------------------------------------------------|-------------------------|--------------------------------------------|---------------------------|----------------------------|---------------|
| S0412/2-041<br>DN200 | Sureflow   | DN 200       | DN200 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |
| S0412/2-042<br>DN225 | Sureflow   | DN 225       | DN225 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |
| S0412/2-043<br>DN250 | Sureflow   | DN 250       | DN250 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Socket x Socket            | 12 Feb 2019   |
| S0412/2-044<br>DN100 | Sureflow   | DN 100       | DN100 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Spigot x Spigot            | 12 Feb 2019   |
| S0412/2-045<br>DN150 | Sureflow   | DN 150       | DN150 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Spigot x Spigot            | 12 Feb 2019   |
| S0412/2-046<br>DN80  | Sureflow   | DN 80        | DN80 Metal Seated Gate Valve                    | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-047<br>DN100 | Sureflow   | DN 100       | DN100 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-048<br>DN150 | Sureflow   | DN 150       | DN150 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-049<br>DN200 | Sureflow   | DN 200       | DN200 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-050<br>DN225 | Sureflow   | DN 225       | DN225 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-051<br>DN250 | Sureflow   | DN 250       | DN250 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-052<br>DN300 | Sureflow   | DN 300       | DN300 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-053<br>DN375 | Sureflow   | DN 375       | DN375 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-054<br>DN450 | Sureflow   | DN 450       | DN450 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-055<br>DN500 | Sureflow   | DN 500       | DN500 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-056<br>DN600 | Sureflow   | DN 600       | DN600 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-057<br>DN750 | Sureflow   | DN 750       | DN750 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-065<br>DN80  | Sureflow   | DN 80        | DN80 Metal Seated Gate Valve                    | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-066<br>DN100 | Sureflow   | DN 100       | DN100 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-067<br>DN150 | Sureflow   | DN 150       | DN150 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-068<br>DN200 | Sureflow   | DN 200       | DN200 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-069<br>DN225 | Sureflow   | DN 225       | DN225 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-070<br>DN250 | Sureflow   | DN 250       | DN250 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-071<br>DN300 | Sureflow   | DN 300       | DN300 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-072<br>DN375 | Sureflow   | DN 375       | DN375 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-073<br>DN450 | Sureflow   | DN 450       | DN450 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-074<br>DN500 | Sureflow   | DN 500       | DN500 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-075<br>DN600 | Sureflow   | DN 600       | DN600 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-076<br>DN750 | Sureflow   | DN 750       | DN750 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-078<br>DN100 | Sureflow   | DN 100       | DN100 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Victaulic x Victaulic      | 12 Feb 2019   |
| S0412/2-079<br>DN150 | Sureflow   | DN 150       | DN150 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Victaulic x Victaulic      | 12 Feb 2019   |
| S0412/2-095<br>DN375 | Sureflow   | DN 375       | DN375 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-096<br>DN375 | Sureflow   | DN 375       | DN375 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-097<br>DN500 | Sureflow   | DN 500       | DN500 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-098<br>DN500 | Sureflow   | DN 500       | DN500 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-099<br>DN600 | Sureflow   | DN 600       | DN600 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-100<br>DN600 | Sureflow   | DN 600       | DN600 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-101<br>DN750 | Sureflow   | DN 750       | DN750 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Brand Name | Nominal Size | Product Description                             | Product Type            | Valve class (Allowable operating Pressure) | Max Operating Temperature | End Connection Designation | Date Endorsed |
|----------------------|------------|--------------|-------------------------------------------------|-------------------------|--------------------------------------------|---------------------------|----------------------------|---------------|
| S0412/2-102<br>DN750 | Sureflow   | DN 750       | DN750 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-103<br>DN450 | Sureflow   | DN 450       | DN450 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-104<br>DN450 | Sureflow   | DN 450       | DN450 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-109<br>DN900 | Sureflow   | DN 900       | DN900 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-112<br>DN900 | Sureflow   | DN 900       | DN900 Metal Seated Gate Valve                   | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-115<br>DN900 | Sureflow   | DN 900       | DN900 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 16                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |
| S0412/2-116<br>DN900 | Sureflow   | DN 900       | DN900 Metal Seated Gate Valve with Bypass valve | Metal Seated Gate Valve | 35                                         | 40°C                      | Flange x Flange            | 12 Feb 2019   |

## AS/NZS 2638.2:2011 - Gate valves for waterworks purposes - Resilient seated

Model identification of the goods on which the STANDARDSMARK may be used:

| Model Identification | Model Name | Brand Name | Product Description                                       | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method                                                  | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|------------------------|-------------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 2055/74              | RSGV       | Sureflow   | DN500 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 500            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap 2/Handwheel 3/Gearbox                               | Option of CC or ACC        | Flange x Flange            | 1 Aug 2017    |
| 2055/74              | RSGV       | Sureflow   | DN600 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 600            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap 2/Handwheel 3/Gearbox                               | Option of CC or ACC        | Flange x Flange            | 1 Aug 2017    |
| 2055/74              | RSGV       | Sureflow   | DN450 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 450            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap 2/Handwheel 3/Gearbox                               | Option of CC or ACC        | Flange x Flange            | 1 Aug 2017    |
| 2055/80              | RSGV       | Sureflow   | DN600 Resilient Seated Gate Valve with DN150 Bypass valve | Resilient Seated Gate Valve | DN 600            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap 2/Handwheel 3/Gearbox                               | Option of CC or ACC        | Flange x Flange            | 1 Aug 2017    |
| 2570/50              | RSGV       | Sureflow   | DN250 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 250            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 2570/50              | RSGV       | Sureflow   | DN225 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 225            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 2570/50              | RSGV       | Sureflow   | DN375 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 375            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 2570/50              | RSGV       | Sureflow   | DN300 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 300            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/50] 2/Handwheel [2570/58] 3/Gearbox [2570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |

Licence No: SMK02420

Issued Date: 6 May 2020

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description               | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method                                                        | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|------------------------|-------------------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 2570/50              | RSGV       | Sureflow   | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/50]<br>2/Handwheel [2570/58]<br>3/Gearbox [2570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 2570/50              | RSGV       | Sureflow   | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80             | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/50]<br>2/Handwheel [2570/58]<br>3/Gearbox [2570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 2570/50              | RSGV       | Sureflow   | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/50]<br>2/Handwheel [2570/58]<br>3/Gearbox [2570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 2570/50              | RSGV       | Sureflow   | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/50]<br>2/Handwheel [2570/58]<br>3/Gearbox [2570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 2570/60              | RSGV       | Sureflow   | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/60]<br>2/Handwheel [2570/68]<br>3/Gearbox [2570/62] | Option of CC or ACC        | Spigot x Spigot            | 1 Aug 2017    |
| 2570/60              | RSGV       | Sureflow   | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/60]<br>2/Handwheel [2570/68]<br>3/Gearbox [2570/62] | Option of CC or ACC        | Spigot x Spigot            | 1 Aug 2017    |
| 2570/60              | RSGV       | Sureflow   | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN080             | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/60]<br>2/Handwheel [2570/68]<br>3/Gearbox [2570/62] | Option of CC or ACC        | Spigot x Spigo             | 22 Mar 2019   |
| 2570/60              | RSGV       | Sureflow   | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/60]<br>2/Handwheel [2570/68]<br>3/Gearbox [2570/62] | Option of CC or ACC        | Spigot x Spigot            | 1 Aug 2017    |
| 2570/60              | RSGV       | Sureflow   | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/60]<br>2/Handwheel [2570/68]<br>3/Gearbox [2570/62] | Option of CC or ACC        | Spigot x Spigo             | 22 Mar 2019   |
| 2570/60              | RSGV       | Sureflow   | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/60]<br>2/Handwheel [2570/68]<br>3/Gearbox [2570/62] | Option of CC or ACC        | Spigot x Spigo             | 22 Mar 2019   |
| 2570/60              | RSGV       | Sureflow   | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/60]<br>2/Handwheel [2570/68]<br>3/Gearbox [2570/62] | Option of CC or ACC        | Spigot x Spigo             | 22 Mar 2019   |
| 2570/70              | RSGV       | Sureflow   | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/70]<br>2/Handwheel [2570/78]<br>3/Gearbox [2570/72] | Option of CC or ACC        | Flange x Socket            | 1 Aug 2017    |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description               | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method                                                        | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|------------------------|-------------------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 2570/70              | RSGV       | Sureflow   | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/70]<br>2/Handwheel [2570/78]<br>3/Gearbox [2570/72] | Option of CC or ACC        | Flange x Socket            | 1 Aug 2017    |
| 2570/70              | RSGV       | Sureflow   | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80             | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/70]<br>2/Handwheel [2570/78]<br>3/Gearbox [2570/72] | Option of CC or ACC        | Flange x Socket            | 1 Aug 2017    |
| 2570/90              | RSGV       | Sureflow   | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/90]<br>2/Handwheel [2570/98]<br>3/Gearbox [2570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |
| 2570/90              | RSGV       | Sureflow   | DN375 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 375            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/90]<br>2/Handwheel [2570/98]<br>3/Gearbox [2570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |
| 2570/90              | RSGV       | Sureflow   | DN400 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 400            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/90]<br>2/Handwheel [2570/98]<br>3/Gearbox [2570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |
| 2570/90              | RSGV       | Sureflow   | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/90]<br>2/Handwheel [2570/98]<br>3/Gearbox [2570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |
| 2570/90              | RSGV       | Sureflow   | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80             | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/90]<br>2/Handwheel [2570/98]<br>3/Gearbox [2570/92] | Option of CC or ACC        | Flange x Flange            | 28 Feb 2017   |
| 2570/90              | RSGV       | Sureflow   | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/90]<br>2/Handwheel [2570/98]<br>3/Gearbox [2570/92] | Option of CC or ACC        | Flange x Flange            | 28 Feb 2017   |
| 2570/90              | RSGV       | Sureflow   | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/90]<br>2/Handwheel [2570/98]<br>3/Gearbox [2570/92] | Option of CC or ACC        | Flange x Flange            | 28 Feb 2017   |
| 2570/90              | RSGV       | Sureflow   | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/90]<br>2/Handwheel [2570/98]<br>3/Gearbox [2570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |
| 2570/90              | RSGV       | Sureflow   | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [2570/90]<br>2/Handwheel [2570/98]<br>3/Gearbox [2570/92] | Option of CC or ACC        | Flange x Flange            | 28 Feb 2017   |
| 2570/96              | RSGV       | Sureflow   | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Handwheel [2570/96]                                               | Option of CC or ACC        | FlangexFlange OS&Y         | 20 Feb 2019   |
| 2570/96              | RSGV       | Sureflow   | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Handwheel [2570/96]                                               | Option of CC or ACC        | FlangexFlange OS&Y         | 20 Feb 2019   |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description                                       | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material                                                     | Valve Operating Method                    | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|-------------------------------------------|----------------------------|----------------------------|---------------|
| 2570/96              | RSGV       | Sureflow   | DN250 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 250            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Handwheel [2570/96]           | Option of CC or ACC        | FlangexFlange OS&Y         | 20 Feb 2019   |
| 2570/96              | RSGV       | Sureflow   | DN300 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 300            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Handwheel [2570/96]           | Option of CC or ACC        | Flange x Flange OS&Y       | 20 Feb 2019   |
| 2570/96              | RSGV       | Sureflow   | DN080 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 080            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Handwheel [2570/96]           | Option of CC or ACC        | FlangexFlange OS&Y         | 20 Feb 2019   |
| 2570/96              | RSGV       | Sureflow   | DN100 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Handwheel [2570/96]           | Option of CC or ACC        | FlangexFlange OS&Y         | 20 Feb 2019   |
| 2570/96              | RSGV       | Sureflow   | DN200 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 200            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Handwheel [2570/96]           | Option of CC or ACC        | FlangexFlange OS&Y         | 20 Feb 2019   |
| 55/74                | RSGV       | AVK        | DN600 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 600            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 1 Aug 2017    |
| 55/74                | RSGV       | AVK        | DN450 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 450            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 1 Aug 2017    |
| 55/74                | RSGV       | AVK        | DN500 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 500            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 1 Aug 2017    |
| 55/80                | RSGV       | AVK        | DN600 Resilient Seated Gate Valve with DN150 Bypass valve | Resilient Seated Gate Valve | DN 600            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 1 Aug 2017    |
| 57                   | RSGV       | AVK        | DN80 Resilient Seated Gate Valve                          | Resilient Seated Gate Valve | DN 80             | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN200 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 200            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Spigot x Spigot            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN150 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 150            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Spigot x Spigot            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN100 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 100            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Spigot x Spigot            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN300 Resilient Seated Gate Valve                         | Resilient Seated Gate Valve | DN 300            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.



# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description               | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material                                                     | Valve Operating Method                    | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|-------------------------------------------|----------------------------|----------------------------|---------------|
| 57                   | RSGV       | AVK        | DN375 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 375            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Socket            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN80 Resilient Seated Gate Valve  | Resilient Seated Gate Valve | DN 80             | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN400 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 400            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |

**Licence No:** SMK02420

**Issued Date:** 6 May 2020

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description               | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material                                                     | Valve Operating Method                    | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|-------------------------------------------|----------------------------|----------------------------|---------------|
| 57                   | RSGV       | AVK        | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Socket            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57                   | RSGV       | AVK        | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57/55                | RSGV       | AVK        | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel           | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57/55                | RSGV       | AVK        | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel           | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description               | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material                                                     | Valve Operating Method          | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|---------------------------------|----------------------------|----------------------------|---------------|
| 57/55                | RSGV       | AVK        | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57/55                | RSGV       | AVK        | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57/55                | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57/55                | RSGV       | AVK        | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57/55                | RSGV       | AVK        | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80             | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC        | Socket x Socket            | 14 Oct 2011   |
| 57/65                | RSGV       | AVK        | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC        | Spigot x Spigot            | 14 Oct 2011   |
| 57/75                | RSGV       | AVK        | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80             | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC        | Flange x Socket            | 14 Oct 2011   |
| 57/90                | RSGV       | AVK        | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57/90                | RSGV       | AVK        | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |

**Licence No:** SMK02420

**Issued Date:** 6 May 2020

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description               | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material                                                     | Valve Operating Method                                               | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 57/90                | RSGV       | AVK        | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80             | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel                                      | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57/90                | RSGV       | AVK        | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel                                      | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57/90                | RSGV       | AVK        | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel                                      | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 57/90                | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel                                      | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| 570/50               | RSGV       | AVK        | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 570/50               | RSGV       | AVK        | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 570/50               | RSGV       | AVK        | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 570/50               | RSGV       | AVK        | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80             | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 570/50               | RSGV       | AVK        | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 570/50               | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 570/50               | RSGV       | AVK        | DN375 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 375            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap [570/50] 2/Handwheel [570/58] 3/Gearbox [570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description               | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method                                                     | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|------------------------|----------------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 570/50               | RSGV       | AVK        | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/50]<br>2/Handwheel [570/58]<br>3/Gearbox [570/52] | Option of CC or ACC        | Socket x Socket            | 1 Aug 2017    |
| 570/60               | RSGV       | AVK        | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/60]<br>2/Handwheel [570/68]<br>3/Gearbox [570/62] | Option of CC or ACC        | Spigot x Spigo             | 22 Mar 2019   |
| 570/60               | RSGV       | AVK        | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/60]<br>2/Handwheel [570/68]<br>3/Gearbox [570/62] | Option of CC or ACC        | Spigot x Spigo             | 22 Mar 2019   |
| 570/60               | RSGV       | AVK        | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/60]<br>2/Handwheel [570/68]<br>3/Gearbox [570/62] | Option of CC or ACC        | Spigot x Spigo             | 22 Mar 2019   |
| 570/60               | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/60]<br>2/Handwheel [570/68]<br>3/Gearbox [570/62] | Option of CC or ACC        | Spigot x Spigot            | 1 Aug 2017    |
| 570/60               | RSGV       | AVK        | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/60]<br>2/Handwheel [570/68]<br>3/Gearbox [570/62] | Option of CC or ACC        | Spigot x Spigot            | 1 Aug 2017    |
| 570/60               | RSGV       | AVK        | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/60]<br>2/Handwheel [570/68]<br>3/Gearbox [570/62] | Option of CC or ACC        | Spigot x Spigot            | 1 Aug 2017    |
| 570/60               | RSGV       | AVK        | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN080             | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/60]<br>2/Handwheel [570/68]<br>3/Gearbox [570/62] | Option of CC or ACC        | Spigot x Spigo             | 22 Mar 2019   |
| 570/70               | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/70]<br>2/Handwheel [570/78]<br>3/Gearbox [570/72] | Option of CC or ACC        | Flange x Socket            | 1 Aug 2017    |
| 570/70               | RSGV       | AVK        | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80             | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/70]<br>2/Handwheel [570/78]<br>3/Gearbox [570/72] | Option of CC or ACC        | Flange x Socket            | 1 Aug 2017    |
| 570/70               | RSGV       | AVK        | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/70]<br>2/Handwheel [570/78]<br>3/Gearbox [570/72] | Option of CC or ACC        | Flange x Socket            | 1 Aug 2017    |
| 570/90               | RSGV       | AVK        | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/90]<br>2/Handwheel [570/98]<br>3/Gearbox [570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description               | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material | Valve Operating Method                                                     | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|------------------------|----------------------------------------------------------------------------|----------------------------|----------------------------|---------------|
| 570/90               | RSGV       | AVK        | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/90]<br>2/Handwheel [570/98]<br>3/Gearbox [570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |
| 570/90               | RSGV       | AVK        | DN400 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 400            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/90]<br>2/Handwheel [570/98]<br>3/Gearbox [570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |
| 570/90               | RSGV       | AVK        | DN375 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 375            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/90]<br>2/Handwheel [570/98]<br>3/Gearbox [570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |
| 570/90               | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/90]<br>2/Handwheel [570/98]<br>3/Gearbox [570/92] | Option of CC or ACC        | Flange x Flange            | 28 Feb 2017   |
| 570/90               | RSGV       | AVK        | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/90]<br>2/Handwheel [570/98]<br>3/Gearbox [570/92] | Option of CC or ACC        | Flange x Flange            | 28 Feb 2017   |
| 570/90               | RSGV       | AVK        | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/90]<br>2/Handwheel [570/98]<br>3/Gearbox [570/92] | Option of CC or ACC        | Flange x Flange            | 10 Apr 2017   |
| 570/90               | RSGV       | AVK        | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/90]<br>2/Handwheel [570/98]<br>3/Gearbox [570/92] | Option of CC or ACC        | Flange x Flange            | 28 Feb 2017   |
| 570/90               | RSGV       | AVK        | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 80             | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Stemcap [570/90]<br>2/Handwheel [570/98]<br>3/Gearbox [570/92] | Option of CC or ACC        | Flange x Flange            | 28 Feb 2017   |
| 570/96               | RSGV       | AVK        | DN100 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 100            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Handwheel [570/96]                                             | Option of CC or ACC        | Flange x Flange OS&Y       | 20 Feb 2019   |
| 570/96               | RSGV       | AVK        | DN080 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 080            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Handwheel [570/96]                                             | Option of CC or ACC        | Flange x Flange OS&Y       | 20 Feb 2019   |
| 570/96               | RSGV       | AVK        | DN300 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 300            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Handwheel [570/96]                                             | Option of CC or ACC        | Flange x Flange OS&Y       | 20 Feb 2019   |
| 570/96               | RSGV       | AVK        | DN150 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 150            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Handwheel [570/96]                                             | Option of CC or ACC        | Flange x Flange OS&Y       | 20 Feb 2019   |
| 570/96               | RSGV       | AVK        | DN250 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 250            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Handwheel [570/96]                                             | Option of CC or ACC        | Flange x Flange OS&Y       | 20 Feb 2019   |
| 570/96               | RSGV       | AVK        | DN225 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 225            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Handwheel [570/96]                                             | Option of CC or ACC        | Flange x Flange OS&Y       | 20 Feb 2019   |
| 570/96               | RSGV       | AVK        | DN200 Resilient Seated Gate Valve | Resilient Seated Gate Valve | DN 200            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158   | Option of 1/Handwheel [570/96]                                             | Option of CC or ACC        | Flange x Flange OS&Y       | 20 Feb 2019   |

**Licence No: SMK02420**

**Issued Date: 6 May 2020**

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.

# SCHEDULE TO STANDARDSMARK LICENCE

| Model Identification | Model Name | Brand Name | Product Description                                             | Product Type                | Nominal Size (DN) | Valve Class (Allowable Operating Pressure) | Maximum Operating Temperature (°C) | Material Designation | Valve Coating Material                                                     | Valve Operating Method                    | Valve Direction of Closure | End Connection Designation | Date Endorsed |
|----------------------|------------|------------|-----------------------------------------------------------------|-----------------------------|-------------------|--------------------------------------------|------------------------------------|----------------------|----------------------------------------------------------------------------|-------------------------------------------|----------------------------|----------------------------|---------------|
| 5790                 | RSGV       | AVK        | DN100 Resilient Seated Gate Valve                               | Resilient Seated Gate Valve | DN 100            | 16                                         | 40°C                               | Ductile Cast Iron    | Polymeric in accordance with AS 4158 - Akzo Nobel Resicoat R-4ES 30 HJF38A | Option of 1/Stemcap 2/Handwheel           | Option of CC or ACC        | Flange x Flange            | 14 Oct 2011   |
| S2570/42-450         | S2570      | Sureflow   | DN450 Resilient Seated Gate Valve With DN100&DN150 Bypass       | Resilient Seated Gate Valve | DN 450            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange Bypass     | 30 Apr 2020   |
| S2570/42-500         | S2570      | Sureflow   | DN500 Resilient Seated Gate Valve With DN100&DN150 Bypass       | Resilient Seated Gate Valve | DN 500            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange Bypass     | 30 Apr 2020   |
| S2570/42-600         | S2570      | Sureflow   | DN600 Resilient Seated Gate Valve with DN100&DN150 Bypass valve | Resilient Seated Gate Valve | DN 600            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange Bypass     | 4 May 2020    |
| S2570/92-450         | S2570      | Sureflow   | DN450 Resilient Seated Gate Valve                               | Resilient Seated Gate Valve | DN 450            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 30 Apr 2020   |
| S2570/92-500         | S2570      | Sureflow   | DN500 Resilient Seated Gate Valve                               | Resilient Seated Gate Valve | DN 500            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 30 Apr 2020   |
| S2570/92-600         | S2570      | Sureflow   | DN600 Resilient Seated Gate Valve                               | Resilient Seated Gate Valve | DN 600            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 30 Apr 2020   |
| S570/42-450          | S570       | AVK        | DN450 Resilient Seated Gate Valve With DN100&DN150 Bypass       | Resilient Seated Gate Valve | DN 450            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange Bypass     | 30 Apr 2020   |
| S570/42-500          | S570       | AVK        | DN500 Resilient Seated Gate Valve With DN100&DN150 Bypass       | Resilient Seated Gate Valve | DN 500            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange Bypass     | 30 Apr 2020   |
| S570/42-600          | S570       | AVK        | DN600 Resilient Seated Gate Valve with DN100&DN150 Bypass valve | Resilient Seated Gate Valve | DN 600            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange Bypass     | 4 May 2020    |
| S570/92-450          | S570       | AVK        | DN450 Resilient Seated Gate Valve                               | Resilient Seated Gate Valve | DN 450            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 30 Apr 2020   |
| S570/92-500          | S570       | AVK        | DN500 Resilient Seated Gate Valve                               | Resilient Seated Gate Valve | DN 500            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 30 Apr 2020   |
| S570/92-600          | S570       | AVK        | DN600 Resilient Seated Gate Valve                               | Resilient Seated Gate Valve | DN 600            | 16                                         | 70°C                               | Ductile Cast Iron    | Polymeric to AS 4158                                                       | Option of 1/Stemcap 2/Handwheel 3/Gearbox | Option of CC or ACC        | Flange x Flange            | 30 Apr 2020   |

End of Record

Licence No: SMK02420

Issued Date: 6 May 2020

This schedule supersedes all previously issued schedules



\* For details of manufacture, refer to the licensee

The STANDARDSMARK is a registered certification trademark of SAI Global Pty Limited (A.C.N. 050 644 642) and is issued under licence by SAI Global Certification Services Pty Limited (ACN 108 716 669) ("SAI Global") 680 George Street, Sydney NSW 2000, GPO Box 5420 Sydney NSW 2001. This certificate remains the property of SAI Global and must be returned to SAI Global upon its request. Refer to the Schedule for the list of product models.