

# SEWERMAX® POLYPROPYLENE PIPES AND FITTINGS

## HANDLING & STORAGE

Although SewerMAX® pipes are notably resistant to impact, they should not be rolled, dropped, thrown, or allowed to come into contact with sharp objects likely to cause damage.

When pipes are unloaded for storage they should be kept in their packs until required. The storage site should be level and free of obstructions. If pipes are not crafted they should be placed on horizontal supporting timbers at approximately 2 metre centres. These timbers can also be used to separate layers when pipes are stacked individually. Stack heights should be limited to prevent excessive ovalisation.

Sockets should be protected from distortion during storage by ensuring all of the sockets are placed at alternate ends and protruding from the stack.

## PACKING SPECIFICATIONS FOR SEWERMAX® PIPES

NOMINAL DIAMETER DN (mm)	APPROXIMATE PACK SIZES			PIPES PER PACK	APPROXIMATE MASS OF PACK (WITHOUT TIMBERS) (kg)	NUMBER OF PIPES PER SEMI-TRAILER
	WIDTH (mm)	HEIGHT (mm)	LENGTH (mm)			
225	1090	630	3300	8	81	256
300	1090	770	3330	6	120	144
375	920 or 1340	950 or 940	3400	4 or 6	118 or 177	90
450	1080	610	3500	2	76	48
525	1890	690	3500	3	150	27
600	2130	770	3400	3	199	27

The information contained in this document should serve as a guide only and is subject to change without notice. For more information please contact Iplex Pipelines Australia Pty Ltd.

